

MATERIAL SAFETY DATA SHEET

FOR EVALUATION PURPOSES ONLY

Revision 1

Prepared 2008-08-06 10:52:53 AM

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: 18 oz Pet Sav'R Csr Lith Product Code: 02700061f

TradeName(s):

SUPPLIER: FOR EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL
CHEMTREC 1-800-424-9300

COMPANY NAME
ADDRESS
CITY, STATE ZIP CODE
PHONE NUMBER

PACKAGED BY:


PLAZE, INCORPORATED
105 BOLTE LANE
ST. CLAIR, MISSOURI 63077
636-629-3400

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name / CAS No</u>	<u>OSHA Exposure Limits</u>	<u>ACGIH Exposure Limits</u>	<u>Other Exposure Limits</u>
ETHYLENE GLYCOL N-BUTYL ETHER, EB 111-76-2 15 - 17 %	25 PPM	20 PPM	
BUTANE 106-97-8 2 - 4 %	800 ppm TWA		
PROPANE 74-98-6 2 - 4 %	1000 ppm PEL 2100 ppm IDLH		

SECTION III - HEALTH HAZARD INFORMATION

EFFECTS OF OVER EXPOSURE: INHALATION: SHORTNESS OF BREATH, DIZZINESS AND LIGHTHEADEDNESS. EYE: CAN CAUSE EYE IRRITATION. SKIN: SLIGHT SKIN IRRITATION, CAN CAUSE DERMATITIS. INGESTION: MAY CAUSE CHEMICAL PNEUMONIA IF ASPIRATED INTO LUNG.



HMIS Rating: 2 - 4 - 0

ACUTE TOXICITY: NOT DETERMINED

Effects of Overexposure, BUTANE:

EYE CONTACT THE GAS PHASE IS NOT EXPECTED TO CAUSE EYE IRRITATION. THE LIQUID PHASE CAN CAUSE FROSTBITE AND BURNS

SKIN CONTACT CONTACT CAN CAUSE SKIN BURNS AND FROSTBITE

Effects of Overexposure, BUTANE:

INHALATION THIS PRODUCT IS AN ASPHYXIATE AND MAY EXHIBIT ANESTHETIC PROPERTIES AT HIGH CONCENTRATIONS.

INGESTION THIS MATERIAL IS GAS UNDER NORMAL ATMOSPHERIC CONDITIONS

Effects of Overexposure, ETHYLENE GLYCOL N-BUTYL ETHER, EB:

EYE CONTACT MAY CAUSE MODERATE EYE IRRITATION WHICH MAY BE SLOW TO HEAL.

SKIN CONTACT PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN IRRITATION. EXCESSIVE EXPOSURE MAY CAUSE HEMOLYSIS, THEREBY IMPAIRING THE BLOOD'S ABILITY TO TRANSPORT OXYGEN.

INGESTION SINGLE DOSE TOXICITY IS CONSIDERED TO BE MODERATE. SMALL AMOUNTS SWALLOWED INCIDENTALLY ARE NOT LIKELY TO CAUSE INJURY. SWALLOWING LARGER AMOUNTS MAY CAUSE INJURY.

INHALATION SINGLE PROLONGED (HOURS) EXCESSIVE INHALATION EXPOSURE MAY CAUSE ADVERSE EFFECTS. EXCESSIVE EXPOSURE MAY CAUSE IRRITATION TO THE UPPER RESPIRATORY TRACT.

Effects of Overexposure, PROPANE:

EYE CONTACT THE GAS PHASE IS NOT EXPECTED TO CAUSE EYE IRRITATION. THE LIQUID PHASE CAN CAUSE FROSTBITE AND BURNS

SKIN CONTACT CONTACT CAN CAUSE SKIN BURNS AND FROSTBITE

INHALATION THIS PRODUCT IS AN ASPHYXIATE AND MAY EXHIBIT ANESTHETIC PROPERTIES AT HIGH CONCENTRATIONS.

INGESTION THIS MATERIAL IS GAS UNDER NORMAL ATMOSPHERIC CONDITIONS

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE RECOGNIZED

EFFECTS OF CHRONIC OVEREXPOSURE: PROLONGED EXPOSURE ABOVE THE OSHA PERMISSIBLE EXPOSURE LIMITS (PEL) MAY RESULT IN KIDNEY AND LIVER DAMAGE

SECTION IV - FIRST AID PROCEDURES

INHALATION: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT GIVE OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION.

EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

SKIN CONTACT: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER.

INGESTION: DO NOT INDUCE VOMITTING. IMMEDIATELY DRINK TWO GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CALL PHYSICAN IMMEDIATELY. KEEP PERSON WARM, QUIET AND GET PROMPT MEDICAL ATTENTION.

SECTION V - FIRE HAZARDS

Flash Point: NOT DETERMINED

Autoignition: NOT DETERMINED

LEL: 1.8 %

UEL: 9.5 %

EXTINGUISHING MEDIA: ALCOHOL FOAM, CO2, DRY CHEMICAL, FOAM OR WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS OF THIS PRODUCT MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

HAZARDOUS COMBUSTION PRODUCTS: BURNING CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE

FIRE FIGHTING: WATER MAY BE USED COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT

SPECIAL EQUIPMENT REQUIRED: WEAR A FULL FACE POSITIVE PRESSURE SELF CONTAINED BREATHING APPARATUS (SCBA) WHEN FIGHTING FIRE

SECTION VI - SPILL OR LEAK PROCEDURES

EMERGENCY ACTION: ISOLATE SPILL OR LEAK AREA IMMEDIATELY. KEEP UNAUTHORIZED PERSONNEL AWAY. VENTILATE AREA AND ELIMINATE ALL IGNITION SOURCES.

SMALL SPILLS: CLEAN UP WITH INERT MATERIALS AND DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

